

DESCRIPTION

CATALOG: E-758-J-259	BALLAST TYPE: Electronic	STARTING METHOD: Instant Start	NUMBER OF LAMPS – LAMP TYPE: 1 - F96T8, 2 - F96T8
-------------------------	-----------------------------	-----------------------------------	--

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE: 347 V~ ±10%	LAMP WATTS: 59 w	INPUT WATTS: 112 w	INPUT CURRENT: 0.335 A	OCV: 715 v	PF: > 0.95	FREQUENCY: 60 Hz	SOUND RATED: A
MIN START TEMP: 32°F / 0°C	CLASS: P	TYPE: 1 outdoor	BALLAST FACTOR: 0.87	BEF: 0.776	LAMP CONNECTION: PARALLEL	THD (1): < 29%	NO PCB'S

(1) FOR 3-F32T8

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES	1.687	8.906	8.344	2.375	9.500	1.500
	TOL(+/-)	0.010	0.010	0.010	0.050	0.050	0.050
	MM	43	226	212	60	241	38
TOL(+/-)	0.25	0.25	0.25	1.30	1.30	1.30	
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	BLUE		
INCHES	22	22	57	47	47		
TOL(+/-)	3/8	3/8	3/8	3/8	3/8		
MM	559	559	1448	1194	1194		
TOL(+/-)	10	10	10	10	10		


CARTON CHARACTERISTICS

UNITS/CARTON 10	CARTONS/LAYER 12+6	# OF LAYERS 7+1	UNITS/PALLET 900	PIECE WEIGHT 2.7 lbs	CARTON WEIGHT 28 lbs	PALLET WEIGHT 2,597 lbs
CARTONS/PALLET 90	CARTON DIMENSIONS 12" x 12" x 4"	PALLET DIMENSIONS 40" x 48" x 7"	PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40" x 48" x 40"			

MISC.

CARTON LABEL

ELECTRICAL DIAGRAM



PRODUCT LABEL



SOLA CANADA

LIGHTING & POWER

171 Ambassador Drive
Units 8 & 9
Mississauga, ON
L5T 2J1

Phone: 905-670-0746
Fax: 905-670-9689
www.solacanada.com

Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Made in Mexico by Industrias Sola Basic S.A. de C.V.

Certificate No. 006281