
CATALOG NUMBER: E-SZA0FT150 FOR ONE 150 WATT, S55 HIGH PRESSURE SODIUM LAMP

Line Voltage	120/277V		
Regulation Line Volts Line Watts	+/- 5% WITHIN TRAPEZOID		
Frequency	60 Hz		
Circuit Type	HX-HPF		
Power Factor (min)	90%		
Insulation Class	H(180°)		
Min. Ambient Starting Temp.	-40° F or -40° C		
Line Voltage (Volts)		120	277
Line Current (Amps) Operating		1.66	0.72
Open Circuit		2.81	1.25
Starting		1.80	0.80
Input Watts (W)		188	188
Open Circuit Voltage (V)		120	120
Drop Out Voltage (V)		96	222
UL(1029) Bench Top Rise		С	В
Recommended Fuse (Amps)		10	4
HIGH POTENTIAL TEST (VOL	TS)		
1Minute	2000		
2 Seconds	2500		
Open Circuit Voltage Tes	st(volts) 110-135		
Short-Circuit Current Tes Secondary Current	st (Amps) 3.6 - 4.6		
		1.25 -	0.52 -
Input Current (Amps)		2.30	1.00

BRACKET

CORE & COIL MOUNTING BRACKET




 $\mathsf{OL}\mathsf{A}$




C-01 MOUNTING CLIP for round case (Furnished as standard with B suffix ballast)

I-01 MOUNTING CLIP for oval case (Furnished as standard with B suffix ballast)



2.50 3.875 8.00 Lead Lengths (inches) 12

CAPACITOR




RATING 14 Mfd \pm 3% 280 VAC MIN Dry Film Capacitor Thermal Plastic Case Max. Case Temp 100° C

IGNITOR 37-63-AS-9.1-N7

Ballast to Lamp Distance (BTL): 2 feet (THERMAL PLASTIC CASE) Max. case Temp:110° C 1¹/₆₄" Case 2 1/2' Oval + 1²⁹/₃₂"→

WIRING DIAGRAM



Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual Performance can vary depending on operating conditions. Specifications are subject to change without notice.



Certificate No. 006281





171 Ambassador Drive Units 8 & 9 Mississauga, ON L5T 2J1

Phone: 905-670-0746 Fax: 905-670-9689

Made in Mexico by Industrias Sola Basic S.A de C.V.