

DESCRIPTION

CATALOG: ERSFC-132-TPK	STARTING METHOD: Rapid Start	INPUT VOLTAGE: 120 V~	OCV: 245 V~	FREQUENCY: 60 Hz
BALLAST TYPE: Normal Power Factor	CLASS: P	TYPE: 1 outdoor	LAMP CONNECTION: Series	SOUND RATED: A
NO PCB'S				

ELECTRICAL CHARACTERISTICS

LAMP TYPE	NUMBER OF LAMPS	LAMP WATTS	MIN. START TEMP. (°F/°C)	INPUT WATTS (Watts)	INPUT CURRENT (Amps)	BALLAST FACTOR	B.E.F.	P.F.	THD %	LAMP CREST FACTOR
FC12T9	1	32	50/10	31	0.61	0.62	2.000	0.42	9	1.5
FC16T9	1	40	50/10	32	0.52	0.64	2.000	0.51	12	1.5

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES	N / A	6.0	5.275	1.937	6.5	1.375
	TOL(+/-)	0.010	0.010	0.010	0.050	0.050	0.150
MM	N / A	153	134	49	165	35	
TOL(+/-)	0.25	0.25	0.25	1.30	1.30	3.80	
LEAD LENGTH							
UNITS	BLACK	WHITE	TERMINALS CONNECTOR				
INCHES	12	30	10				
TOL(+/-)	3/8	3/8	3/8				
MM	304	762	254				
TOL(+/-)	10	10	10				

CARTON CHARACTERISTICS

UNITS/CARTON 16	CARTON/LAYER 12	# OF LAYERS 5	UNITS PALLET 960	PIECE WEIGHT 2.3 lbs	CARTON WEIGHT 38 lbs	PALLET WEIGHT 2 315 lbs
CARTON PALLET 60	CARTON DIMENSIONS 12" x 12" x 4"	PALLET DIMENSIONS 40" x 48" x 7"	PALLET DIMENSIONS LOADED , INCLUDING WOOD PALLET 40" x 48" x 28"			


MISC.

With Wire Harness and Circline Socket.

CARTON LABEL



ELECTRICAL DIAGRAM



PRODUCT LABEL



Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Made in Mexico by Industrias Sola Basic S.A. de C.V.



Certificate No. 006281

SOLA CANADA

LIGHTING & POWER

171 Ambassador Drive
Units 8 & 9
Mississauga, ON
L5T 2J1

Phone: 905-670-0746
Fax: 905-670-9689

www.solacanada.com